

KENOVEL[®]

Compensateur revêtu Type S-PTFE

DN50 - DN1000



DN	L	Mouvement axial		Mouvement latéral	Mouvement angulaire	Pression max	Température max
		Compression	Elongation				
mm/pouce	mm	mm	mm	mm	mm	Bar	°C
50 / 2"	130/150	20	10	12	10°	12	130
65 / 2"½	130/150	20	10	12	10°	12	130
80 / 3"	130/150	20	10	12	10°	12	130
100 / 4"	130/150	20	10	12	10°	12	130
125 / 5"	130/150	25	12	12	10°	12	130
150 / 6"	130/150/200	25	12	12	9°	12	130
200 / 8"	130/150/200	25	12	12	7°	10	130
250 / 10"	130/150/200	25	12	12	5°	10	130
300 / 12"	130/150/200	30	15	15	5°	10	130
350 / 14"	200	30	15	15	5°	10	130
400 / 16"	200	30	15	15	4°	8	130
450 / 18"	200	30	15	15	4°	8	130
500 / 20"	200	30	15	15	3°	8	130
550 / 22"	250	35	17	15	3°	8	130
600 / 24"	250	35	17	15	3°	8	130
650 / 26"	250	35	17	15	3°	7	130
700 / 28"	250	35	17	15	3°	7	130
750 / 30"	250	35	17	15	2°	7	130
800 / 32"	250	35	17	15	2°	7	130
850 / 34"	250	35	17	15	2°	7	130
900 / 36"	250	35	17	15	2°	7	130
950 / 38"	250	35	17	15	2°	7	130
1000 / 40"	250	35	17	15	2°	7	130

Toute dimension possible